

ADVR72104

1SATA 2MP 5in1 H.264 DVR Series 7



Features:

- Support 4ch 1080N real-time encoding;
- Support AHD, TVI, CVI, CVBS, IP video input;
- Support VGA maximum 1080P output, HDMI 1080P output
- HDMI/VGA simultaneous video output;
- 1U Case, 1 SATA(Up to 8TB);
- 1*10/100Mbps auto-sensing Ethernet port, RJ45 port
- Automatic networking support, a key to add equipment;
- Support the Onvif protocol;
- Support GB28181 (Optional);
- Cloud services, P2P, alarm information push to phone;
- Support remote access, support ARSP;
- Support DHCP, FTP, DNS, DDNS, NTP, UPNP, EMAIL, 3G, WIFI, IP search, Alarm center, etc ;
- Mobile phone remote monitoring (iOS, Android);
- Multi browser access (IE, Chrome, Firefox, Safari);
- Support for more than twenty languages;
- Perfect protection circuit,unique triple watchdog function
- Support WEB, CMS, VMS, MYEYE Platform;
- Support coaxial control

Specification

| | | |
|------------|---------------|---|
| | Model | ADVR72104 |
| Video | Codec | H.264 |
| | Video Input | [AHD] , [TVI] , [CVI] , [IP] (ONVIF) |
| | Live View | 4*1080N@25fps 4*720P@12fps 4*960H@25fps |
| | Encode | 4*1080N@25fps 4*720P@12fps 4*960H@25fps |
| | Multi-mode | Analog: 4CH*1080N@25fps / 4CH*720P@12fps / 4CH*960H@25fps |
| | | Hybrid: 2CH*720P(Analog) + 2CH*720P(IP Camera) |
| | | IP: 8CH*1080P / 8*720P / 4CH*1080P / 4CH*720P |
| | Playback | 4CH |
| Audio | Compression | Audio: G.711a |
| | Intercom | Support |
| Management | Record mode | Manual > Alarm > Motion Detection>Timing |
| | Inquire mode | Inquire by Time / Calendar / Event / Channel |
| | Storage mode | HDD Storage, Network Storage |
| | Backup | Network, USB, SATA |
| Interface | Video input | 4*BNC |
| | HDMI output | 1*HDMI (MAX:1080P) |
| | VGA output | 1*VGA (MAX:1080P) |
| | Audio I/O | 4/1 |
| | Alarm I/O | 0/0 |
| | Ethernet port | 1*10/100Mbps Ethernet port, RJ45 port |
| | PTZ control | 1*RS485 Support for multiple PTZ protocol |
| | USB Port | 2*USB2.0 ports |
| | HDD | 1*SATA interface (Up to 8TB) |
| General | Temperature | 0 °C to 55 °C |
| | Humidity | 10% -90% RH |
| | Power supply | 12V/2A |
| | Consumption | <10W (Without HDD) |
| | Weight | ~ 1KG |
| | Dimension | 255mm(L)* 236mm(W)* 44mm(H) |