


SC25-AI-RF

3MP Wi-Fi Camera Remote Call



Key Features

- 3MP High resolution image 360° Full view
- Full-duplex 2-way real time talk
- 256GB TF card storage up to 44 days record.
- Support Cloud Storage
- Support Wi-Fi Hotspot offline use.
- Dual light infrared & LED white light
- Sleep Mode for privacy protection
- ONVIF 2.4
- High Accuracy >95% Human Detection and Tracking
- Call to cellphone by Call Button & Wireless Remote Control



Specifications

Model	SC25-AI
Video	
Imaging devices	1/2.9 CMOS Sensor
Video encoding standards	H.265
System format	PAL 50HZ/NTSC 60HZ
Effective resolution	2304*1296 (3MP)
Video frame rate	15fps
Video streaming	135kbps-2048kbps
Minimum illuminance	Day mode 1Lux, Night mode 0.01Lux
Day and night mode	Auto
Video output	P6SLite Mobile APP / EasyVMS PC Client
Capture function	Support
Audio	
Encoding standard	G.711U
Audio input	Build-In microphone
Voice calls	Tap to talk / Two-way audio
Recording management	
Recording Mode	by Time Schedule, by Human Detect, by Motion detect
Video saving	Micro SD card / PC / NVR(Onvif)
Cloud Storage	Support
Alarm	
Alarm detection	Human detect alarm high accuracy >95%
Sound and light alarm	Sound alarm, Light alarm, Sound & Light alarm
Alarm voice	Record alarm sound from APP / Use system alarm voice
Alarm event action	Start record event, Capture image send to email, Upload to FTP server



Gimbal	
Preset bits	Supports 6 preset bit settings
Trace function	Support Human tracking and turn back to home position.
Internet	
WIFI	2.4G antenna support, 802.11 b/g/n
Protocol Support	ONVIF, P6S
Call	
One-click call	Calling button on camera dial to Smart Phone APP
Sleep	
Sleep function	Supports scheduled sleep and immediate sleep functions to maintain user privacy
Other	
TF card capacity	Supports up to 256GB
Operating voltage	USB 5V
Video recordings space	5.75GB/Day (32GB = 5Days, 64GB = 11Days, 128GB = 22Days, 256GB = 44Days)
Work environment	-10°C - +45°C
General	
Dimensions	103mm*94mm*153mm (with box)
Weight	Approximately 0.35 kg
Carton Measure	535 mm x490 mm x 330 mm (50pcs/ctn)

Dimensions

